

Z-LBH30S200 DAY/NIGHT BULLET IP CAMERA





FEATURES

- 1/2.9" SONY Low Illumination CMOS Sensor
- Hisilicon Processor (Hi3516C)
- H.264 / H.265 Compression
- 2.8mm (3.6mm, 6mm Optional)
- 3 Megapixel HD Lens, HDR, Built-in POE
- Main Stream: 1080P@30fps With IR-Cut
- 42μ x 2PCS Long Range IR LED, IR range: 30M

Z-LBH30S200 DAY/NIGHT BULLET IP CAMERA



Model NO.	Z-LBH30S200
Camera	
Image Sensor	1/2.9" SONY Low Illumination CMOS Sensor
Main processor	HISILICON Hi3516C
Resolution	2MP 1080P
Effective Pixels	1985(H)*1105(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Lens	
Focus Length	2.8mm (3.6mm, 6mm Optional)
Focus Control	Fixed
Lens Type	Fixed
Pixels	3M Pixels
Night Vision	
Infrared LED	42μ X 2PCS
Infrared Distance	30M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Support IEEE 802.3af
Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@30fps
Sub Stream 1	720*480@30fps
Tri Stream	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
	ורוטופ, ורמע, אוערטע, אוערטע רמע
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config.	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Corridor Pattern	Support
Defog Mode	Support
BLC	Support
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	English, Chinese Simplified, Chinese Traditional, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederland's
General	
Housing	Metal, IP66
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	
	157(W) x 70(H) x 66(D)mm
Weight	650g

Introducing an easy-to-install,cost effective way to monitor indoor or outdoor actiivity whether it's in near complete darkness, uneven light, or bright direct sunshine.

Equipped with 2 long-range IR LEDs, the new Z-LBH30S200 camera captures outstanding, highly detailed video images virtually anywhere. It delivers the enhanced capabilities, reliability and ease-of-installation been searching for in a day/night bullet camera. Proven auto white balance meet the requirements of most application the can be installed virtually anywhere indoors or outdoors — thanks to a IP66 housing built of the highest quality ADC12 Aluminum that resists water, moisture, dust and vandalism. And its backed by two-years warranty.



SUGGESTED APPLICATIONS



- Parking lots
- Public places
- Commercial
- Government buildings
- Military
- many more...

©2013 Zebra Security, Inc. All rights reserved. All products and names mentioned ae the property of their rrespecte owners. While Zebra has made every efffort at the time of publication to ensure the accuracy of the information povided herein, product specifications, confi gurations, priceystem/component/ent/options availability are all subject to change without notice.

Zebra Security Inc. USA Surveillance & IP video products, imaging systems division 120 Comostock Ave Station Island New York 10314, USA www.zebrasecurity.us



