



# Z-NW1253RP

DAY/NIGHT BULLET IP CAMERA



## IP66 Rated

*Weatherproof  
bullet camera*



### FEATURES

- Support Onvif V2.0 protocol
- 30FPS @ 1080P Full HD
- POE (IEEE802.3af)
- H.265 Video compression format, high compression ratio
- Support variable stream bit rate, network bandwidth adaptive
- 2-axis adjustable bracket, adapt to ceiling mount and wall mount
- AWB, AE, AGC, BLC, 3D-NR
- Dual ICR filters, Day/night mode auto switching
- Support multi-users remote access vis PC CMS software, Web browsers
- Support remote access via IOS & Android APP
- Support data storage by FTP Server, DAS, PC Hard disk, NVR

# Z-NW1253RP

## DAY/NIGHT BULLET IP CAMERA



10.30 am



08.30 pm

Day/night imaging automatically drops color in low light for greater detail. Coupled with the 24 IR LEDs, it allows you to continuously record 24/7.



Model No	Z-NW1253RP
<b>Camera</b>	
Imaging sensor	1/2.8" Aptina AR0237 CMOS
Processor	Hisilicon 3516C
Max. Pixels	2 Megapixel, 1920x1080
Frame rate	30FPS
Min. Illumination	Color:0.1Lux@F1.7, Black & White: 0Lux (IR LEDs On)
Lens Specs	Fixed Lens 3.6mm
Infrared LEDs	24 IR LEDs, IR range 30M
ICR Filter	Dual Optical Filters, Day/Night modes auto switch
Shutter speed	1/25 ~ 1/100,000 second
S/N Ratio	> 50dB
<b>Video</b>	
Video Encoding	H.265/H.264 format
Dual stream	Main Stream 2Mbps~6Mbps, Sub Stream 512kbps~2.5Mbps (adjustable)
Image Capture	JPEG format (picture definition is same with video)
Noise reduction	3D-NR
AGC& WB& Exposure	Auto Gain Control, Auto White Balance, Auto Exposure
<b>Audio/Alarm</b>	
Audio I/O	G.711A, 64Kbps
Alarm sensor I/O	Optional
<b>Network</b>	
Ethernet	Adaptive 10/100M RJ45
POE (IEEE802.3af)	POE
Interface Standard	Onvif version 2.0
Network Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,UPnP,SMTP,SNMP,IGMP,P2P
System Safety	Password protection
Watermarking	Support
System Authority	Permission level: Administrator, Common User
Alarm Event	Motion Detect, Video Loss, Video Cover, Network Abnormal
Alarm Responses	Snapshot, Email Alert, Start to Record, FTP Upload
Recording modes	Manual, Schedule, Motion Detect, Network Abnormal
Storage methods	Upload to FTP Server, NVR, NAS, PC Hard disk
Remote Access	PC CMS Software, Web Browsers (IE, Chrome, Firefox, Safari, Opera), IOS & Android APP, Support QR Code Scanning
<b>Interface</b>	
LAN	1 RJ45 10m/100m Ethernet Port
<b>General</b>	
Bracket	3-axis manual adjustable bracket, wire goes through internally
Installation type	Ceiling mount, Wall mount
Housing Material	Superior aluminum alloy, Good cooling effect
Ingress Protection	IP66
Application	Outdoor and Indoor, Waterproof IP67
Working temperature	-30°C ~ 60°C
Humidity	< 95% (No condensing)
Power Supply	DC Female interface, DC12V±10%
Gross Weight	0.85 KG (Box Size 15.5 x 15.5 x 13CM)
	Made in Taiwan

Introducing an easy-to-install, cost effective way to monitor indoor or outdoor activity, whether it's in near complete darkness, uneven light, or bright direct sunshine.

Equipped with 24 long-range IR LEDs, the new Z-NW1253RP camera captures outstanding, highly detailed video images virtually anywhere. It delivers the enhanced capabilities, reliability and ease-of-installation that you have been searching for in a day/night bullet camera. Proven auto white balance meet the requirements of most applications. Best of all, the can be installed virtually anywhere — indoors or outdoors— thanks to a IP66 housing built of the highest quality ADC12 aluminum that resists water, moisture, dust and vandalism. And its backed by a two-year warranty.

### SUGGESTED APPLICATIONS

- Parking lots
- Public places
- Commercial
- Streets
- Government buildings
- Military
- many more...

#### Zebra Security Inc. USA

Surveillance & IP video products, imaging systems division  
120 Comostock Ave Station Island  
New York 10314, USA  
[www.zebrasecurity.us](http://www.zebrasecurity.us)

