



Z-ZND1243RP

VANDALPROOF IR DOME IP CAMERA

Full HD
1080P



DAY/NIGHT SURVEILLANCE

24-7 VIDEO
IMAGING

The Z-ZND1243RP is the perfect choice where a high-resolution color mini-dome camera is required that is fast and simple to install

FEATURES

- Support Onvif V2.0 protocol
- 25FPS@1080P Full HD
- POE (IEEE802.3af)
- H.265 dual Video compression format, high compression ratio
- Support variable stream bit rate, network bandwidth adaptive
- 3-axis adjustable bracket, adapt to ceiling mount and wall mount
- AWB,AE,AGC,BLC,3D-NR
- Dual ICR filters, Day/night mode auto switching
- Support multi-users remote access vis PC CMS software, Web browsers
- Support remote access via IOS & Android APP
- Support data storage by FTP Server, DAS, PC Hard disk, NVR

Z-ZND1243RP

VANDALPROOF IR DOME IP CAMERA



The economically meets the needs of retail and other commercial applications. Z-ZND1243RP, This indoor color mini-dome delivers highly versatile, cost-effective, and fully integrated surveillance in a simple-to install package. It is attractive and unobtrusive yet provides a crime-detering presence

MAIN FEATURES

- High-tech, attractive styling
- Tamper resistant cover
- 1/2.8" Color CCD
- Minimum illumination 0.1 lux
- Day-night imaging
- 1080P Full HD resolution
- Compact, simple-to-install design
- 2 years limited warranty

Model No Z-ZND1243RP	
Camera	
Imaging sensor	1/2.8" Aptina AR0237
Processor	Hisilicon 3516C
Max. Pixels	2.0MP, 1920*1080
Frame rate	25FPS
Min. Illumination	Color:0.1Lux@F1.7, Black & White: 0Lux (IR LEDs On)
Lens Specs	Fixed 2.8mm
Infrared LEDs	30m night vision
ICR Filter	Dual Optical Filters, Day/Night modes auto switch
Shutter speed	1/25 ~ 1/100,000 second
S/N Ratio	> 50dB
Video	
Video Encoding	H.265/H.264 format
Dual stream	Main Stream 2Mbps~6Mbps, Sub Stream 512kbps~2.5Mbps (adjustable)
Image Capture	JPEG format (picture definition is same with video)
Noise reduction	3D-NR
AGC & WB & Exposure	Auto Gain Control, Auto White Balance, Auto Exposure
Audio/Alarm	
Audio I/O	G.711A, 64Kbps
Alarm sensor I/O	Optional
Network	
Ethernet	Adaptive 10/100M RJ45
POE (IEEE802.3af)	POE
Interface Standard	Onvif version 2.0
Network Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, P2P
System Safety	Password protection
Watermarking	Support
System Authority	Permission level: Administrator, Common User
Alarm Event	Motion Detect, Video Loss, Video Cover, Network Abnormal
Alarm Responses	Snapshot, Email Alert, Start to Record, FTP Upload
Recording modes	Manual, Schedule, Motion Detect, Network Abnormal
Storage methods	Upload to FTP Server, NVR, NAS, PC Hard disk
Remote Access	PC CMS Software, Web Browsers (IE, Chrome, Firefox, Safari, Opera), iOS & Android APP, Support QR Code Scanning
Interface	
LAN	1 RJ45 10m/100m Ethernet Port
General	
Bracket	3-axis manual adjustable bracket, wire goes through internally
Installation type	Ceiling mount, Wall mount
Housing Material	Superior aluminum alloy, Good cooling effect
Application	Outdoor and Indoor, Waterproof IP66
Working temperature	-30°C ~ 60°C
Humidity	< 95% (No condensing)
Power Supply	DC Female interface, DC12V±10%
Gross Weight	1.4KG (Box Size 29.5 x 17.5 x 12CM) Made In Taiwan



APPLICATIONS

- Retail outlets
- Indoor malls
- Casinos
- Food franchises
- Office buildings
- Grocery stores
- Apartments/condominiums



©2013 Zebra Security, Inc. All rights reserved. All products and names mentioned are the property of their respective owners. While Zebra has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice.

Zebra Security Inc. USA

Surveillance & IP video products, imaging systems division
120 Comostock Ave Station Island
New York 10314, USA
www.zebrasecurity.us

