



# ZDIR20P70

VANDALPROOF IR DOME CAMERA



DAY/NIGHT SURVEILLANCE

**24-7** VIDEO  
IMAGING

*The **ZDIR20P70** is the perfect choice where a high-resolution color mini-dome camera is required that is fast and simple to install*

- Heavy duty metal housing
- High-tech, attractive styling for retail, corporate and other indoor applications
- Labor saving, easy mounting
- 1/3" Color CCD
- 2M Pixels Board lens 3.6 mm/ F 2.0
- 700 TV lines horizontal resolution
- c 5x 24 Pb IR LED, IR Distance: 20 M
- Minimum illumination 0.5 lux with tinted dome
- Shipped fully assembled and ready to install
- 2 year limited warranty

# ZDIR20P70

VANDALPROOF IR DOME CAMERA



The ZDIR20P70 economically meets the needs of retail and other commercial applications. This indoor color mini-dome delivers highly versatile, cost-effective, and fully integrated surveillance in a simple-to install package. It is attractive and unobtrusive yet provides a crime-detering presence round-the-clock with its daynight imaging protection.

## MAIN FEATURES

- High-tech, attractive styling
- Tamper resistant cover
- 1/3" Color CCD
- Minimum illumination 0.5 lux
- Day-night imaging
- 700 TVL horizontal resolution
- Compact, simple-to-install design
- 2 year limited warranty

Model	ZDIR20P70
Camera	
Image Sensor	1/3" COLOR CCD
Horizontal Resolution	700TV Lines
Effective Pixels	P/N: 350KP, 728(H)×488(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/50-1/100, 000Sec; NTSC 1/60-1/100, 000Sec
Sync System	Internal
Usable Illumination	0.5Lux/F1.2
S/N Ratio	≥48dB
Gamma Correction	0.45
Scanning System	PAL: 625 Lines, 50 Field/Sec; NTSC: 525 Lines, 60 Field/Sec
Video Output	Composite Signal (1.0Vp-p, 75Ω)
Lens	
Focus Length	3.6mm (4/6/8/12/16mm optional)
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels
Night Vision	
Infrared LED	φ 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Camera Features	
Day/Night	Color/ B&W
White Balance	AUTO
Gain Control	AUTO
General	
Vandalproof Housing	YES
IR Cut Filter	YES
Operation Temperature	-10℃ ~ +50℃ RH 95% Max.
Power Source	DC12V±10%, 700mA
Dimension	94x69(H)mm
Weight	400g
Origin	Taiwan



## APPLICATIONS

- Retail outlets
- Indoor malls
- Casinos
- Food franchises
- Office buildings
- Grocery stores
- Apartments/condominiums



©2013 Zebra Security, Inc. All rights reserved. All products and names mentioned are the property of their respective owners. While Zebra has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice.

**Zebra Security Inc. USA**  
Surveillance & IP video products, imaging systems division  
120 Comstock Ave Station Island  
New York 10314, USA  
[www.zebrasecurity.us](http://www.zebrasecurity.us)

